

The scalable enterprise server

NEC Express5800/A2000 Series

EXCEPTIONAL PERFORMANCE, FLEXIBILITY AND AVAILABILITY FOR ENTERPRISE USE



EXCEPTIONAL PERFORMANCE

HIGH AVAILABILITY

ADVANCED FLEXIBILITY

Perfect Fit for Enterprise Use

NEC Express5800/A2000 Series is an enterprise-class quad-socket 4U rack server based on the Intel® Xeon® Processor E7 v2 Product Family. The server offers the highest level of performance, availability, and flexibility for compute-intensive and memory-hungry applications in mission critical and virtualized environment.

Flexible for Optimized Use

NEC Express5800/A2000 Series is highly flexible to support ever demanding and dynamically changing on-premise or cloud workloads for large databases, analytics, and large-scale virtualization. Capacity Optimization (COPT) provides ability to flexibly optimize the resources by allowing cores to be enabled dynamically. On-line addition of resources such as CPU cores, memory module, and IO cards offers flexibility to fit your business needs.

Exceptional Performance

- NEC Express5800/A2000Series is a scale-up server design with a massive resource pool to support compute-intensive and memory-hungry applications in mission critical and virtualized environments.
- Powered by the Intel® Xeon® Processor E7 v2 Product Family and inheriting NEC's supercomputer high performance technology, the NEC's sixth generation enterprise server supports up to 4 processors / 60 cores / 120 threads, 4.0 terabyte of memory, and 16 PCIe 3.0 slots.

High Availability

- NEC Express5800/A2000Series offers industry-leading reliability, availability, and serviceability (RAS) features required to support business-critical workloads for enterprise computing.
- Combining Intel's Run Sure technology with NEC's mainframe inspired advanced RAS features, the Express5800/A2000 Series server with built-in service processors and many redundant components offers exceptional availability and serviceability on standard operating systems.

Advanced Flexibility

- NEC Express5800/A2000Series is highly flexible to support ever demanding and dynamically changing on-premise or cloud workloads for large databases, analytics, and large-scale virtualization.
- Custom configurations offer ability to populate 2, 3 or 4 sockets, and enable or disable cores based on performance requirements.
- Provide pay as you grow configurations

HARDWARE SPECIFICATION

MODEL	Express5800/A2000 Series (A2040b, A2040b COPT, A2020b)
Form factor / height	4U rack
Number of Processors	A2040b: 2 to 4 (configurable), A2020b: 2 (fixed)
Processors	Intel® Xeon® Processor E7-4890 v2 (2.8 GHz/15-core/37.5 MB) Intel® Xeon® Processor E7-4870 v2 (2.3 GHz/15-core/30 MB) Intel® Xeon® Processor E7-4860 v2 (2.6 GHz/12-core/30 MB) Intel® Xeon® Processor E7-4830 v2 (2.2 GHz/10-core/20 MB) Intel® Xeon® Processor E7-4820 v2 (2.0 GHz/8-core/16 MB) Intel® Xeon® Processor E7-4809 v2 (1.9 GHz/6-core/12 MB) Intel® Xeon® Processor E7-8891 v2 (3.2 GHz/10-core/37.5 MB) Intel® Xeon® Processor E7-8893 v2 (3.4 GHz/6-core/37.5 MB)
Memory Type	DDR3L-1600 Registered DIMM (8/16GB), DDR3L-1600 Load Reduced DIMM (32GB), DDR3L-1066 Load Reduced DIMM (64GB *) * 64GB DIMM is to be supported in 1H/2014
Memory Slots	64
Maximum memory	4TB
Storage type	Hot plug 2.5-inch SAS HDD, Hot-plug 2.5-inch SAS SSD
Maximum internal drive bays	8
Maximum internal storage	HDD: 9.6TB, SSD: 3.2TB
Removable media	Internal or external drive (option)
Expansion slots	14x PCI Express 3.0 (x8 lane, x8 socket) (Low Profile, 167.6mm in length) 2x PCI Express 3.0 (x4 lane, x8 socket) (Low Profile, 167.6mm in length)
Video (VRAM)	Embedded in management controller chip (8MB)
Network	2x Management LAN connector (1000BASE-T/100BASE-T/10BASE-T, RJ45, rear)
Power	Up to 4 80 PLUS® Platinum certified power supply / Redundancy and hot plug supported
Maximum power consumption (200V)	A2040b:2335VA / 2288Watt, A2020b:2208VA / 2164Watt
Interface	5x USB 2.0 (3x front, 1x rear, 1x internal), 1x VGA (front), 1x SUV (2x USB /1x VGA/1x Serial, rear)
Dimensions (W x D x H)	443.0 x 719.3 x 174.5 mm (4U rack height) 482.6 x 892.5 x 175.5 mm (including protruding objects and guide rails)
Maximum weight	A2040b:55kg, A2020b:55Kg
Temperature and humidity conditions (non-condensing)	Operating: 10 to 40 ° C/ 50 to 104 ° F , 20 to 80% Non-operating: -10 to 55° C/14 to 131° F, 20 to 80%
Operating systems and virtualization software	Microsoft® Windows Server® 2008 R2 (SP1 or later) Standard / Enterprise / Datacenter Microsoft® Windows Server® 2012 Standard / Datacenter Red Hat® Enterprise Linux® 6.4 or later (x86_64) Oracle® Linux 6.4 / UEK R2 or later (x86_64) VMware® ESXi™ 5.1 Update 2 VMware® ESXi™ 5.5

©Copyright 2014 NEC Corporation. The information and specification contained in this publication are subject to modification without prior notice. Microsoft and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Intel, Intel Logo, Pentium, Pentium Inside, Xeon, and Xeon Inside are trademarks of Intel Corporation in the U.S. and/or other countries. Linux is a trademark of Linus Torvalds. Red Hat is a registered trademark of Red Hat, Inc. in the U.S. VMware is a registered trademark or trademark of VMware, Inc. in the United States and/or other jurisdictions. All other names of products and brands cited are the property of their respective owners. NEC is not responsible for photographic or typing errors.

Asia (APAC) NEC Corporation

7-1, Shiba 5-chome Minato-ku
Tokyo 108-8001 Japan

www.nec.com/express

Europe (EMEA) NEC Enterprise Solutions

Anton Philipsweg 1
1223 KZ Hilversum
The Netherlands
+31 35 6899111

www.nec-enterprise.com

North America NEC Corporation of America Information Technology Group

2880 Scott Blvd.
Santa Clara, CA 95050 U.S.
+1 866 632 3226

www.necam.com/servers